

# HERED®

## Articulating Boom Lift

# HA19J

GB/CE/ANSI Compliance



## HIGH LIGHTS

- Wide range boom compound action.
- Four-wheel drive, Floating axle design, Better off - road performance.
- Integrated Rotary reducer makes Smooth turning and adapt to dust environment.
- High-precision Load sensing system to avoid mis-halt.

## FEATURES

### Standard Configuration

Horn  
Proportional control  
Motion Alarm  
Flashing beacons  
Self-lock gate  
Emergent descent  
Emergent stop  
Automatic leveling platform  
Fault diagnostic  
Load sensing system  
GPS  
Tilting protection system  
Oscillating axle  
Released type engine tray  
Color display

### Optional

AC power to the platform  
Air tube to the platform

*Grand in Sound  
Sharp in Heart  
Viture in Action*

[sales@hrdlift.com](mailto:sales@hrdlift.com)

[www.hered-lift.com](http://www.hered-lift.com)

# HERED®

## Articulating Boom Lift HA19J

GB/CE/ANSI Compliance

Models	HA19J
<b>Measurements</b>	
Max. Working Height	20.77m
Platform Height	18.77m
Horizontal Reach	12m
Max. Up and Over	8.1m
A-Length (Stowed)	9.0m
B-Width (Stowed)	2.49m
C-Heights (Stowed)	2.697m
D-Platform Length	2.4m
E-Platform Width	0.9m
F-Wheel Base	2.5m
G-Ground Clearance	0.31m
<b>Performance</b>	
Platform Capacity	250kg
Drive Speed (Stowed)	6.5km/h
Gradeability (Stowed)	45%
Turning Radius (In.)	2.42m
Turning Radius (Out.)	5.57m
Turntable Rotation	360°
Platform Rotation	±90°
H-Turntable Tail Swing	0
Tilt Sensor Activation Max.	5°
Operating Wind Speed	12.5m/s
<b>Power</b>	
Engine	Kubota V2403
Power	36.5kw
<b>Tires</b>	
Tyres	355/550625
<b>Weight</b>	
Weight	11000kg
Hydraulic Tank Capacity	130L
Fuel Tank Capacity	120L

