

# HERED®

## Electric RT Scissors HS1218ERT

GB/CE/ANSI Compliance

### HIGHLIGHTS

- Drive on all terrains.
- Large ground clearance, stronger passing ability.
- AC motor drive, smooth driving, great micro mobility.
- 8 packs of batteries, more durable and last longer.

### FEATURES

#### Standard

Automatic Braking	Emergency Stop	Flashing Beacons
Proportional Control	Rolling-out Deck	Tilt Sensor
Emergency Descent	Folding Guardrails	Safety Alarm
Hour Meter	Self-diagnosis	Self-lock Gate
Motion Alarm	Charging Protection	Horn
GPS		

#### Optional

Working Lamp on the Platform  
Load Sensing System  
AC Power to the Platform  
Air Tube to the Platform  
Outriggers



*Grand in Sound  
Sharp in Heart  
Viture in Action*

[sales@hrdlift.com](mailto:sales@hrdlift.com) [www.hered-lift.com](http://www.hered-lift.com)

# HERED®

## Electric RT Scissors HS1218ERT

GB/CE/ANSI Compliance

Models	HS1218ERT
<b>Measurements</b>	
<b>Max. Working Height</b>	14.19m
<b>A-Max. Platform Height</b>	12.19m
<b>B-Platform Length</b>	2.92m
<b>C-Platform Width</b>	1.65m
<b>Extension Size</b>	0.91m
<b>D-Overall Height(Rails Up)</b>	2.81m
<b>Overall Height(Rails Down)</b>	2.01m
<b>E-Overall Length(With Ladder)</b>	3.15m
<b>F-Overall Width</b>	1.75m
<b>G-Wheel Base</b>	2.3m
<b>H-Ground Clearance</b>	0.2m
<b>Productivity</b>	
<b>Platform Capacity</b>	362kg
<b>Extension Capacity</b>	113kg
<b>Max. Occupancy</b>	3
<b>Drive Speed (Stowed)</b>	4.8km/h
<b>Drive Speed (Raised)</b>	0.6km/h
<b>Turning Radius (in.)</b>	2.29m
<b>Turning Radius(out.)</b>	4.88m
<b>Up/Down Time</b>	54/50s
<b>Gradeability</b>	35%
<b>Max. Slope</b>	2°/3°
<b>Control</b>	Proportional Control
<b>Drive</b>	Front Wheels
<b>Multi Disc Brake</b>	Front Wheels
<b>Tires</b>	240/55—17.5
<b>Power</b>	
<b>Batteries</b>	8x6V/370Ah
<b>Charger</b>	100-240VAC/35A
<b>Weight</b>	
<b>Weight</b>	5500kg

