

# HERED®

Articulating Boom Lift

## HA14JE

GB/CE/ANSI Compliance



### HIGHLIGHTS

- AC motor drive, smooth driving, great micro mobility.
- High-precision load sensing system, less accidental false alarms and shutdowns.
- Stable rotation with integrated rotary reducer, Comprehensive protection.
- Suitable for dust environment, Zero emission, stable operation and energy saving.
- Large capacity batteries, strong endurance.

### FEATURES

#### Standard

Horn  
Proportional Control  
Motion Alarm  
Flashing Beacons  
Self-lock Gate  
Emergency Descent  
Emergency Stop  
Automatic Leveling Platform  
Self-diagnosis  
Load sensing system  
GPS

#### Optional

AC Power to the Platform  
Air Tube to the Platform

*Grand in Sound  
Sharp in Heart  
Viture in Action*

[sales@hrdlift.com](mailto:sales@hrdlift.com) [www.hered-lift.com](http://www.hered-lift.com)

# HERED®

## Articulating Boom Lift HA14JE

GB/CE/ANSI Compliance

| Models                      | HA14JE         |
|-----------------------------|----------------|
| <b>Measurements</b>         |                |
| Max. Working Height         | 15.7m          |
| Platform Height             | 13.7m          |
| Horizontal Reach            | 7.24m          |
| Max. Up and Over            | 7.7m           |
| A-Length(Stowed)            | 6.42m          |
| B-Width(Stowed)             | 1.75m          |
| C-Height(Stowed)            | 2.01m          |
| D-Platform Length           | 1.52m          |
| E-Platform Width            | 0.76m          |
| F-Wheel Base                | 2.01m          |
| G-Ground Clearance          | 0.2m           |
| <b>Performance</b>          |                |
| Platform Capacity           | 230kg          |
| Drive Speed(Stowed)         | 5.2km/h        |
| Gradeability(Stowed)        | 30%            |
| Turning Radius(Inside)      | 0.8m           |
| Turning Radius(Outside)     | 3.8m           |
| Turntable Rotation          | 355°           |
| Platform Rotation           | ±90°           |
| H-Turntable Tailswing       | 0              |
| Tilt Sensor Activation Max. | 3°             |
| Operating Wind Speed        | 12.5m/s        |
| <b>Power</b>                |                |
| Batteries                   | 8×6V/370Ah     |
| Charger                     | 100-240VAC/35A |
| <b>Tires</b>                |                |
| Tires                       | 240/55-17.5    |
| <b>Weight</b>               |                |
| Weight                      | 7070kg         |
| Hydraulic Tank Capacity     | 20L            |

